Acta Technologica Agriculturae 4
Nitra, Slovaca Universitas Agriculturae Nitriae, 2015, pp. 118–121

VACUUM FLUCTUATION IN 2 × 13 HERRINGBONE MILKING PARLOUR IN DEPENDENCE ON VACUUM CONTROL METHOD

Jiří FRYČ*, Josef LOS, Radovan KUKLA, Jan KUDĚLKA

Mendel University in Brno, Czech Republic

Vacuum fluctuation was measured using three different vacuum control methods. Firstly, the use was made of a control valve delivered by the manufacturer; then, an additionally installed frequency converter was used. Lastly, a frequency converter fitted with the stabilisation device prototype was used. First, control sensitivity according to ISO was measured in all the three alternatives. Then, vacuum fluctuation during milking was measured. To conduct the measurements under objectively identified conditions, another measurement was conducted with air feed during milking being replaced with a precisely defined variable flow rate. The conducted measurement confirmed the fact that when the frequency converter is used, vacuum fluctuation in stabilised condition is at the same level as when the control valve is used. If there are sudden changes in flow rate and the frequency converter is used, vacuum fluctuation increases. The proposed stabilisation device prototype can reduce the fluctuation in small milking plant but it is not suitable in large milking parlours.

Keywords: vacuum fluctuation; vacuum control methods; frequency converter

Presently, frequency converters are commonly applied to drive the milking machine vacuum pumps as this results in major electricity cost reduction. Their frequent application is encouraged by their relatively low price and resulting short payback periods. Rasmussen (2005) states that the payback period is approx. 4.8 years. Olejník and Pavelková (2008) later gave a payback period of 2 years. Since then, the prices of frequency converters have dropped even further and their payback period is currently even less than one year (Kudělka *et al.*, 2012). The use of frequency converters results in power cost reduction ranging around 50%. Olejník and Pavelková (2008) give a cost reduction value of 50–58%. To a certain extent, the reduction percentage is affected by the vacuum pump delivery given by the size of the milking plant. If an unnecessarily high performing vacuum pump is selected, reduction appears to be high, too. To compare various systems, reduction should be calculated in relation to the performance of the vacuum pump defined in accordance with the standard ISO 5707 (ÚNMZ, 1999a). Rasmussen measured the absolute reduction and states that the automatic milking system DeLaval VMS showed a saving of 20 kWh of electric power over 24 hrs of frequency conveyer-driven vacuum pumps being in use (Rasmussen, 2005). The vacuum pump revolution control has been dealt with for a relatively long time (Dunn, 1996), and research in the field of milking has focused on vacuum control in individual teat cups (Ströbel *et al.*, 2012, 2013). In practice, certain problems are still encountered when using frequency converters.

Vacuum control by changing the revolutions entails certain deterioration in vacuum stability. Vacuum fluctuation is reflected in the deformation curve of the teat liner. The teat liner deformation curve in dependence on vacuum was

described by Karas *et al.* (2003a, 2003b). Greater vacuum fluctuation is determined by the fact that air flow rate changes, i.e. during the teat cup application, occur very fast and changes in the electric motor and vacuum pump revolutions take place at a slower pace, which is caused by the rotating part inertia. Therefore, milking machines with frequency converters are also fitted with a conventional control valve, which is set to a value that is by ca 1 kPa higher than the vacuum level set for the frequency converter control. If the air flow rapidly drops, vacuum would be increasing for a short period of time. The control valve prevents from the increase exceeding 1 kPa. Contrariwise, when the flow rate increases, no system preventing from vacuum drop is available and vacuum changes depend on the time over which the vacuum pump revolutions reach the desired value.

To validate the proper functioning of the stabilisation device, vacuum fluctuation was measured in a 2 × 3 tandem milking parlour with very good results. Therefore, the objective of this study is to validate the applicability of the manufactured stabilisation device prototype in a large milking plant using a frequency converter to control the vacuum.

Material and methods

The stabilisation device prototype was manufactured by the utility model 14020 (Fryč, 2004). To validate the proper functioning of the stabilisation device, vacuum fluctuation was measured in a 2 × 13 herringbone milking plant. The milking plant is equipped with two oil lubricated rotary vane vacuum pumps with an actual delivery of 2230 l min⁻¹

Contact address: *Jiří Fryč, Mendel University in Brno, Faculty of Agronomy, Department of Agricultural, Food and Environmental Engineering, Zemědělská 1, 613 00 Brno, Czech Republic, e-mail: fryc@mendelu.cz

at a 50 kPa vacuum. Working vacuum in the milking parlour was 45 kPa. The milking machine vacuum system capacity (milk pipe, air pipe, air tank, receiver) totals 395 l. Three vacuum control alternatives were measured:

1. control valve delivered by the manufacturer;
2. additionally installed frequency converter; and
3. frequency converter complete with the stabilisation device prototype.

Firstly, control sensitivity according to the ISO standard was measured for all the three alternatives. Each measurement was conducted three times and the mean value was calculated. Secondly, vacuum fluctuation during milking was measured. The vacuum fluctuation measurement was conducted by means of the Pulsatortester PT IV instrument measuring the vacuum for a period of 60 s and over this time interval we determined the maximum, average and minimum vacuum values. Vacuum fluctuation was then calculated as a difference between the maximum and minimum value.

Given the fact the air flow rate in the milking device changes in the course of milking in dependence on the operations being performed, the course of changes is irregular and also depends on the skills of milkers. To get comparable results, the measurements of each alternative were divided into the two following groups:

- a) milking performed only during the measurements; and
- b) milking and teat cup application performed during the measurements.

In the group a) as well as in the group b), a total of ten measurements were performed and statistically processed by the Tukey test in order to assess the statistical significance of differences among all the measurement combinations.

Figure 1 Volume of air sucked in by the milking machine

Although intervals with an approximately identical activity were selected during milking, the air flow was not absolutely the same. In particular, when attaching the teat cups, the flow rate values may strongly differ and application time may also be different. To conduct the measurements in objectively identical conditions, another measurement was carried out with air consumption during milking being replaced by a precisely defined variable flow rate, see Figure 1.

An electromagnetic valve connected instead of the collector to the central suction piece provided for variable flow. The operation of the electromagnetic valve was controlled by a time relay. Ten-second opening intervals alternated with ten-second closing intervals. Once in the open position, the valve sucked 290 l min⁻¹. The total air flow was then gradually increased by activating pulsators and sucking in air via three different calibrated openings. More air got into the milking machine vacuum system through the leaking spots. The measurement determined that each activated pulsator sucked in

22.4 l min⁻¹, the calibrated openings sucked in 200 l min⁻¹, 400 l min⁻¹ and 600 l min⁻¹ respectively, leakage sucked in 160 l min⁻¹. The milking machine setup for the measurement is shown in Table 1.

Each measurement was repeated ten times and the measured values were statistically processed. To process the data, a use was made of the dispersion analysis which was employed to determine the statistical significance of the difference between the measured values determined by the individual vacuum control methods. The method of subsequent testing using the Tukey range test assessed the statistical significance of differences between all the measurement combinations.

Results and discussion

The control sensitivity measurement conducted according to ISO 6690 (ÚNMZ, 1999b) resulted in the following average values. When the control valve was used, the value totalled 0.38 kPa, when the frequency

Table 1 Milking machine setup for the measurement

Measurement	Milking machine setup	Minimum air flow in l min⁻¹	Maximum air flow in l min⁻¹
1	26 pulsators	742	1032
2	26 pulsators + 200 l min⁻¹	942	1232
3	26 pulsators + 400 l min⁻¹	1142	1432
4	26 pulsators + 600 l min⁻¹	1342	1632

Figure 2 Vacuum fluctuation at milking

Figure 3 Vacuum fluctuation at a variable flow rate

converter was used, the value totalled 0.42 kPa, and when the frequency converter with the stabilisation device was used, the value was 0.46 kPa. Reaching the very low values resulted from the fact that the control valve is not located at the vacuum pump, but directly in the plant. The frequency converter vacuum sensor is also fitted in the milking plant. The differences are minimal and this measurement is better in assessing the functioning of control in a stabilised condition. Olejník and Pavelková (2008) stated that the use of a frequency converter improved the sensitivity by 15%. Our results did not confirm this. In our measurements, the measured values

were very low and the differences were not statistically significant in any of the cases.

The results of the vacuum fluctuation measurement are shown in Figure 2. The blue column shows the fluctuation during milking without attaching the teat cups during the measurement. In these cases, vacuum fluctuation is very low. The lowest value of 0.44 kPa was achieved with the frequency converter control. Values below 0.6 kPa were also achieved in the other measurements, though. The differences were not statistically significant in any of the cases.

Completely different results were achieved when the teat cups were

applied during the vacuum fluctuation measurement. The best results were achieved when using regulation based on the control valve when the mean vacuum fluctuation value reached 1.25 kPa. When the frequency converter was used, this value rose to 2.38 kPa. By applying the stabilisation device, the mean vacuum fluctuation value does not dropped down, but went up to 3.25 kPa. Differences between all the values are statistically highly significant. Olejník and Pavelková (2008) state that vacuum fluctuation during the frequency converter control goes up to 2 kPa but they do not specify conditions under which the values were measured. Kukla (2007) gives the vacuum fluctuation up to 2.5 kPa. Our measured results are similar.

When the vacuum fluctuation measurement was carried out under a precisely defined variable air flow rate, the lowest values were achieved when the control valve was used. The difference between the maximum and minimum vacuum value regardless of the milking machine setup was approximately 0.6 kPa. During frequency converter control, the first three measurements fluctuated around 1.5 kPa. With the increasing flow rate, it increased to values exceeding 2.5 kPa. By connecting the prototype of the stabilisation device clearly indicates that the fluctuation magnitude depends on the air flow rate through the milking machine. In the measurements no. 1–4, fluctuation ranged between 1.92 kPa and 4.20 kPa.

To process the data, we employed the dispersion analysis based on which we determined the statistically highly significant difference in the measured values between the individual vacuum control methods. After that, we tested the differences between the specific control methods at the identical flow rate. The testing method – Tukey test – revealed statistically highly significant differences between all measurements combinations at all the set flow rates.

Conclusion

The measurement we performed confirms that if a frequency converter is used, vacuum fluctuation in the stabilised condition is at the same level as when a control valve is used. If sudden flow rate changes occur and the frequency converter is used,

vacuum fluctuation increases, which relates to the fact that the time needed to change the vacuum pump and electric motor number of revolutions is longer than the time it takes to change the control valve opening. Likewise, it has been demonstrated that the proposed prototype of the stabilisation device is not suitable in large milking parlour.

Summary

Vacuum fluctuation was measured using three different vacuum control methods. Firstly, the use was made of a control valve delivered by the manufacturer; then, an additionally installed frequency converter was used. Lastly, a frequency converter fitted with the stabilisation device prototype was used. First, the control sensitivity according to ISO was measured in all the three alternatives. Then, vacuum fluctuation during milking was measured. To conduct the measurements under objectively identified conditions, another measurement was conducted with air feed during milking being replaced with a precisely defined variable flow rate. Using this mode, we measured a total of four different levels of fluctuating flow rates. Using the control sensitivity measurement according to ISO, we reached values below 0.5 kPa and the differences between the individual control methods were statistically non-significant.

The results of the vacuum fluctuation measurement during milking were first evaluated during ongoing milking without attaching the teat cups during the measurement. In all cases, vacuum fluctuation was below 0.6 kPa. The differences between the average values were not statistically significant. When the teat cups were attached during the measurement, the average value of vacuum fluctuation using the control valve regulation was 1.25 kPa. When the frequency converter was used, this value increased to 2.38 kPa. By connecting the stabilisation device this value increased to 3.25 kPa. The differences between all the values were statistically highly significant.

When vacuum fluctuation was measured under precisely defined variable airflow rate values and a control valve was used, vacuum fluctuation reached approximately 0.6 kPa regardless of the milking machine setup. When a frequency converter was used for control purposes, vacuum fluctuation values were in the entire measured range between 1.32 kPa and 1.77 kPa. Only during the measurement with the highest flow rate did fluctuation rise to 2.5 kPa. By connecting the stabilisation device prototype, it was identified that fluctuation depended on the airflow rate through the milking machine. At lower flow rates, vacuum fluctuation ranged around 2 kPa. The increasing flow rate entailed an increase to values going beyond 4 kPa. Mutual differences between all values were statistically highly significant.

The conducted measurement confirmed the fact that when the frequency converter is used, vacuum fluctuation in the stabilised condition is at the same level as when the control valve is used. If there are sudden changes in flow rate and the frequency converter is used, vacuum fluctuation increases. It has been demonstrated that the proposed prototype of the stabilisation device is not suitable in large milking parlour.

Acknowledgment

This study was financed by the Internal Grant Agency of the Faculty of Agronomy, Mendel University in Brno No. TP 11/2013.

References

- DUNN, D. 1996. Farmers save energy with VFD dairy vacuum pump. In *Resource Engineering and Technology for a Sustainable World*, vol. 3, no. 11, pp. 13–14.
- FRYČ, J. 2004. Zařízení k regulaci podtlaku u dojícího stroje a redukční ventil pro zařízení k regulaci podtlaku u dojícího stroje. Int. Cl. 7: A01 J 5/007 Úřad průmyslového vlastnictví Česká republika 14020. 09. 02. 2004.
- KARAS, I. – LOBOTKA, J. – GÁLIK, R. 2003a. Výsledky testovania niektorých konštrukčných prvkov dojacej techniky. Nitra: Slovenská poľnohospodárska univerzita v Nitre.
- KARAS, I. – GÁLIK, R. – BACSKOROVÁ, J. 2003b. Analysis of factors influencing a thickness of teat-cup liner flattening during dynamic straining. In *Acta Technologica Agriculturae*, vol. 6, no. 2, pp. 51–54.
- KUDÉLKA, J. – FRYČ, J. – KUKLA, R. – KONRÁD, Z. – ŠEVČÍK, J. 2012. Controls operation of vacuum pump of the milking machine by frequency converter. In *MendelNet 2012: Proceedings of International Ph.D. Students Conference*. Brno: Mendel University, pp. 1101–1107. Available at: http://mnet.mendelu.cz/mendelnet2012/articles/38_kudelka_595.pdf
- KUKLA, R. 2007. Vliv změny regulace elektromotoru na odběr elektrické energie. In *Acta Mechanica Slovaca*, vol. 11, no. 4-D, pp. 555–559.
- OLEJNÍK, P. – PAVELKOVÁ, N. 2008. Využití měničů frekvence ABB v dojárnách Fullwood. In *Elektro odborný časopis pro elektrotechniku*, vol. 18, no. 7, pp. 32–33.
- RASMUSSEN, J. B. 2005. Electricity and water consumption by milking. In *Physiological and Technical Aspects of Machine Milking: Proceeding of the international conference held in Nitra, Slovak Republic*, pp. 147–152.
- STRÖBEL, U. – ROSE-MEIERHÖFER, S. – ÖZ, H. – BRUNSCH, R. 2013. Development of a control system for the teat-end vacuum in individual quarter milking system. In *Sensors (Switzerland)*, vol. 13, no. 6, pp. 7633–7651.
- STRÖBEL, U. – ROSE-MEIERHÖFER, S. – HOFFMANN, G. – AMMON, C. – AMON, T. – BRUNSCH, R. 2012. Vacuum application for individual quarters in modern milking system. In *Landtechnik*, vol. 67, no. 6, pp. 405–408.
- ÚNMZ. 1999a. Dojící zařízení – Konstrukce a provedení. ČSN ISO 5707. Praha: Úřad pro technickou normalizaci, metrologii a státní zkušebnictví.
- ÚNMZ. 1999b. Dojící zařízení – Mechanické zkoušky. ČSN ISO 6690. Praha: Úřad pro technickou normalizaci, metrologii a státní zkušebnictví.