Field testing of a magnesium oxide-lime-calcium chloride hydrochloric acid based filter

Margandan KARUNANITHI^a, Rachana AGRAWAL^a, Keshaw SINGH^a, Saroj SHARMA^a, Kushal QANUNGO^{*a}, and Rajeev ACHARYA^b.

^a Department of Applied Science and Humanities, Faculty of Engineering and Technology, Mody Institute of Science and Technology (Deemed University), Lakshmangarh-332311, Dist. Sikar, Rajasthan, India

^b Department of Science and Technology, Govt. of Rajasthan, 506, 4th Floor Mini Secretariat, Bani-Park, Jaipur, Rajasthan, India

Abstract Field trials of a MgO-Lime-CaCl₂-HCl filter has been carried out to test the operation of the filter during actual user conditions. Water quality parameters like pH, TDS, Ca, Mg hardness, total alkalinity, SO₄²⁻, Cl⁻ were found to be within permissible limits in the water obtained from the filter except nitrate, whose concentration was above permissible limits in the raw ground water itself. The dosage of HCl had to be adjusted and fixed in the field trials. In comparison to the laboratory trials conducted earlier it was found that during the field trials there was on an average 6% reduction in the fluoride removal efficiency of the filter. Operational user problems of filter were found and were addressed in the village.

Keywords: magnesium oxide, water quality parameters, removal fluoride efficiency

1. Introduction

Fluoride is both beneficial and harmful to human health [1, 2, 3]. Its beneficial effects include its role in the formation of enamel etc. when present within desirable limits, however when present in excess it causes fluorosis a musculoskeletal disease characterized by weakening of bones, teeth inability to do physical labour etc [1, 4].

The World Health Organization sets the desirable limits of fluoride as 0.5 to 1.00 ppm and maximum permissible limit of 1.5 ppm [5], while in India the Bureau of Indian standards (BIS) sets the desirable concentration at 1 ppm and maximum permissible limits 1.5 ppm [6]. According to Indian Standard Organization (ISO) the desirable range is 0.6 to 1.2 ppm and maximum permissible limits is 1.5 ppm [7]. Ground water in many places in the world contain fluoride above permissible limits [8]. In India the groundwater in the state of Rajasthan

has higher fluoride concentration in 32 districts of its 33 districts [9, 10, 11].

Reverse Osmosis, Ion exchange, Activated alumina, Nalgonda Technique, Bone char, Clay bricks are known to remove fluoride from water and are used for defluoridation purposes [2, 12]. In view of the higher fluoride concentration in groundwater in Lakshmangarh Tehsil of Sikar district of Rajasthan, the Department of Science and Technology, Govt. of India has sponsored the laboratory and field trials of a magnesium oxide based defluoridation filter that has been recently developed at IISc Bangalore (India) [13, 14, 15]. The process involves adding calculated quantities of MgO, lime and aqueous solution of CaCl₂ to the fluoride contaminated ground water. The water is left overnight and the filtered to another container and NaHSO₄ is added to adjust the pH to within potable limits of 6.5 to 8.5 [13, 14, 15].

In view of the higher total alkalinity of local ground water, a suitable ratio of MgO, Lime and CaCl_2 solution has been arrived at in the laboratory. NaHSO_4 was replaced by dil HCl due to excess of SO_4^{2-} in the pH adjusted water. Laboratory trials of this technique has been conducted and has been recently reported [16]. To evaluate the performance of the filter under actual user conditions, we conducted field trials in the village Pilaniyon ki Dhani in Shola village of Lakshmangarh. In this paper we report the preliminary result of field trials and compare it with laboratory trials conducted earlier [16].

2. Experimental

The fluoride filter was fabricated using the technique describes earlier [17]. The filter was installed in the covered verandah of a house in Pilaniyon ki Dhani (Village Shola).

The household was provided with seven bottles 7.5% CaCl_2 in demineralised water, 0.38 N HCl in demineralised water and seven packets of 50,000.0 mg MgO + 37,500.0 mg lime mixture. The household was told to keep the chemicals out of reach of children in safe manner. The operation of the filters was first demonstrated and thereafter the head of the household was trained to operate the filter. It was observed that it took 2-3 days for consuming 50 liter water by a family of five adults and three children. The performance of the filter was monitored in the field for two weeks. The raw water and pH adjusted fluoride free water was brought from the village in a clean stoppered food grade PET container and analysed in the laboratory.

Fluoride was measured using an Ion Selective Electrode (Orion-Thermo Scientific, USA) using TISAB III as buffer. Fluoride standards of 1 and 10 ppm were prepared from 100 ppm F^- standard (Orion-Thermo Scientific, USA) for calibration. pH, was measured using Hanna pH meter (USA) and calibrated using a buffer capsules of pH 7 (CDH India Ltd.) in demineralised water. TDS was measured using Hanna electronic TDS meter and calibrated using 1000 ppm KCl solution in

demineralised water. Calcium hardness was determined by EDTA (0.02 N) using Patton and Reiders reagent (AR, CDH India Ltd.). Magnesium was determined using EDTA (0.02 N) using EBT Indicator (AR, CDH India Ltd.). Alkalinity was determined by titrating with dil H_2SO_4 (0.02N) using phenolphthalien indicator. Chloride was determined by titrating with AgNO_3 (0.0268 N) solution prepared using AR grade AgNO_3 (CDH India Ltd.). Sulphate was determined by turbidity method ($\text{BaCl}_2 \cdot 2\text{H}_2\text{O}$ Qualigens India Ltd.) using a digital photo-colorimeter (Instrument India Ltd.) by measuring absorbance at 220 nm and 270 nm. K^+ and Na^+ were determined by a flame photometer (ESICO, India), calibrated using 50 ppm Na^+ and 20 ppm K^+ solutions. Nitrate was analyzed using a Shimadzu 1800 UV-VIS Spectrophotometer by measuring the absorbance at wavelengths at 220nm and 270nm (1 N HCl is added to prevent interference due to OH^- or CO_3^{2-}).

3. Results and Discussions

Before field work was performed six trials laboratory experiments were carried out using water brought from the village. The raw water and MgO-CaO- CaCl_2 treated water was analysed for various water quality parameters. It was found that in the final pH adjusted water the measured quality parameters (the pH, TDS, Ca, Mg, hardness, CO_3^{2-} , HCO_3^- , Total alkalinity, SO_4^{2-} , Cl^-) were within the permissible limits except nitrate, whose concentration in the raw water itself was high. After the laboratory trials of the filter were successful, the filter was put to field testing.

During laboratory trials it was found that 600 to 620 ml of 0.38 N HCl was sufficient to lower the pH of 45 liters MgO-CaO- CaCl_2 treated water to 8.1 in six trials. Under field conditions it was found in 7 trials that 660ml of 0.38 N HCl was required for to bring down the pH to an average value of 7.9 (**Fig. 1.**)

Notice that in field trials and lab trials the reduction of F^- concentration occurred by 65% and 59% respectively (**Fig. 2.**).

Fig. 1. Comparative pH values of raw and pH adjusted water during Laboratory and Field Trials in Vill. Pilaniyon ki Dhani.

Fig. 2. Comparative F⁻ values of raw and pH adjusted water during Laboratory and Field Trials in Vill. Pilaniyon ki Dhani.

Fluoride removal in this process is a combined precipitation of $\text{Mg}(\text{OH})_{2-x}\text{F}_x$ [18] [19] [20] and CaF_2 [21]. There is considerable reduction of HCO_3^- ion concentration (**Fig. 3**).

Fig. 3. Comparative HCO_3^- values of raw and pH adjusted water during Laboratory and Field Trials in Vill. Pilaniyon ki Dhani.

In the treated water as compared to the raw water in field trials and lab trials (by 627 ppm and 668 ppm respectively) due to the formation of insoluble CaCO_3 ; Eq. (1).

Notice that the carbonate ion concentration in treated water reduces as compared to the raw water, (both by 41 ppm and 25 ppm) in field and lab trials **Fig. 4** as some of the carbonate possibly gets precipitated as CaCO_3 due to the presence of added calcium in water: Eq. (2).

Also, there is a carbonate bicarbonate equilibrium occurring in the water due to addition of basic lime in the first step and hydrochloric acid in the second step. For the above mentioned reasons the Total Alkalinity decreases by 57 ppm and 62 ppm in treated water as compared to raw water both for field and lab trials (**Fig. 5**).

Fig. 4. Comparative CO₃²⁻ values of raw and pH adjusted water during Laboratory and Field Trials in Vill. Pilaniyon ki Dhani.

Fig. 5. Comparative TA(CaCO₃ eqv) values of raw and pH adjusted water during Laboratory and Field Trials in Vill. Pilaniyon ki Dhani.

The added calcium in form of calcium chloride and lime gets precipitated in the form of CaCO₃ (discussed above) and hence there is reduction Ca⁺² ion concentration by 66 ppm and 64 ppm in field and lab trials respectively (**Fig. 6.**)

The Mg⁺² concentration in raw water and treated remains nearly constant (increases very slightly by 1 ppm, (**Fig. 7**) due to very low solubility of Mg(OH)₂ in water ($K_{sp}=5.0 \times 10^{-12}$) [22].

On addition of MgO, CaO and 7.5% CaCl₂ solution the pH of water rises to 10.0-11.3. During this stage the precipitation of Mg(OH)₂ and CaCO₃ occurs as the solubility of Mg(OH)₂ [23] and CaCO₃ is very low in pH greater than 10 [24]. In this step the fluoride removal also occurs as fluoride ions gets trapped in the interstitial spaces of Mg(OH)₂ and also HCO₃⁻¹ gets converted to CaCO₃ and gets removed from the solution[15]. The precipitated salts are removed by filtration, however, at this pH the water is not potable (drinkable). The drinkable range of water is between 6.5 to 8.5 as per WHO [5] and ISO standards [6]. Therefore dil. HCl is being added to adjust the pH to within potable limits. Also, at this pH range, the solubility of Mg(OH)₂ or CaCO₃ is sufficient to prevent their precipitation [23,24].

In line with above the Total Hardness decreases by 18 ppm in treated water as compared to raw water both for field and lab trials (**Fig. 8**).

Fig. 6. Comparative Ca⁺² values of raw and pH adjusted water during Laboratory and Field Trials in Vill. Pilaniyon ki Dhani.

Fig. 7. Comparative Mg²⁺ values of raw and pH adjusted water during Laboratory and Field Trials in Vill. Pilaniyon ki Dhani.

Fig. 9. Comparative Cl⁻ values of raw and pH adjusted water during Laboratory and Field Trials in Vill. Pilaniyon ki Dhani.

Fig. 8. Comparative Total Hardness values of raw and pH adjusted water during Laboratory and Field in Vill. Pilaniyon ki Dhani.

Due to pH adjustment by HCl the chloride concentration increases considerably by 99 ppm in field trials as compared 123 ppm in lab trial (**Fig. 9**).

The sulphate concentration slightly increases by 10 ppm in treated water as compared to raw water (**Fig. 10**).

Fig. 10. Comparative SO₄²⁻ values of raw and pH adjusted water during Laboratory and Field Trials in Vill. Pilaniyon ki Dhani.

This may be due to the introduction of sulphate in form of impurities in lime (commercial grade) and technical grade of MgO used. The nitrate concentration was more than the permissible limit of

(100 ppm) and ranged from 128 to 132 ppm (**Fig. 11**).

Fig. 11. Comparative NO_3^- values of raw and pH adjusted water during Laboratory and Field Trials in Vill. Pilaniyon ki Dhani.

The TDS values of the treated water increased marginally by 127 and 131 ppm in field and lab trials respectively **Fig. 12**.

Fig. 12. Comparative TDS values of raw and pH adjusted water during Laboratory and Field Trials in Vill. Pilaniyon ki Dhani.

Na^+ and K^+ ion concentration did not change significantly and were in the range of 400-500 ppm and 13-14 ppm respectively.

When filter with single tap was put in field trial the cloth got choked repeatedly. Therefore two taps were fitted with six layers of cloth. No choking of the cloth was subsequently observed. For convenience, a line was drawn outside the drum using a waterproof permanent marker to indicate 50 liter volume of water for easy filling of water. Every time after the upper container was emptied, the settled sludge and water at the bottom of the container (approximately 5L) was removed, and stored in a 60 liter plastic container and covered. When the plastic sludge container became full the supernatant water was decanted and disposed off in a common drain outside the house. The fluoride concentration in the supernatant water was found to be 1.49 and 1.51 ppm in two sludge buckets that were emptied during the trials. The sludge was taken back to the laboratory for safe disposal in form of cement stabilized sludge mud blocks to be made later.

There was a considerable effort in filling the water in the filter as the house had only one common tap at a very low level in the courtyard and there was no overhead tank in the house. Filling the filter with water using a pipe was not possible as the water supply was at very low pressure. A bucket with a 10 liter mark outside was provided to fill the water into the drum from the common tap. To reduce the effort in filling the water in the filter, the filter was relocated from the open verandah of the house to a thatched shed near the water tap.

It was observed that when the villagers operated the filter, the six layer cloth tied at the mouth of the tap fell off several times due to the pressure of water in the upper container. Therefore it was important to tie the cloth securely using a strong rope or twine to the tap. Since the location of the village is remote, it was necessary to keep spare plastic pipes, taps and Teflon tape for securing the threads of the plastic pipes in case of leakage and breakage. Only a slight change of taste of water from the filter as compared to raw water was observed.

An important advantage of this filter process as compared to activated alumina filter is that the

fluoride removal efficiency remains almost constant when used repeatedly as fresh dosage of adsorbents and chemicals are added, whereas in activated alumina based filters the fluoride removal capability of the filter gradually decreases. Though no bacteriological studies were carried out, chances of bacterial contamination is low as each day the filter has to be washed and refilled afresh with water and chemicals. The filter media also does not need any periodic regeneration moreover the process does not need any skilled personnel for operation.

4. Conclusions

To conclude we have carried out the user field trials of the MgO-Lime-CaCl₂-HCl base filter and found that HCl dosage had to readjusted in field trails. Also there is a slight reduction (6%) in the efficiency of the filter. Otherwise the filter performance almost similarly to the trails conducted in the laboratory earlier. Practical issues of filling the water in the filter, crucial aspect of improper tying of six layers cloth, disposal of sludge and water mixture from the filter, acceptability of the filter in term of tastes of water and user friendliness were understood and out resolved within the limitations of a single user trials described above.

5. Acknowledgments

Financial help from (Water Technology Initiative) DST, Govt. of India is acknowledged in form of project No. (DST/DT/WTI/2k8/95). The authors thank the MITS for providing facilities and support. Prof. S. Sudhakar Rao, IISc, Bangalore is thanked for advice and support.

6. References

*Email: kushalq@rediffmail.com

- [1]. J. Fawell, K. Bailey, J. Chilton, E. Dahi, L. Fewtrell and Y. Magara, Fluoride in Drinking Water. WHO, Geneva, 2006.
- [2]. A.K. Susheela, *A Treatise on Fluorosis, Fluorosis*, 3rd Eds, Research and Rural Development Foundation, New Delhi, 2007.
- [3]. I. Enache, S. Birghila and A. Dumbrava, Ovidius University Annals of Chemistry, **20**,146-152(2009)
- [4]. K.S. Kothari, Fluorosis Affecting Health/teeth of Children and People in Rural Rajasthan, <http://www.journalistkothari.com/DEFAULT.htm> (date accessed 23rd Sept. 2012)
- [5]. *** Guidelines for Drinking-Water Quality Incorporating 1st and 2nd Addenda, Vol.1, Recommendations.–3rded.WHO, Geneva, 2008.http://www.who.int/water_sanitation_health/dwq/gdwq3rev/en/
- [6]. *** Drinking Water Specification Second Revision of IS 10500) [http://bis.org.in/sf/fad/FAD25_\(2047\)C.pdf](http://bis.org.in/sf/fad/FAD25_(2047)C.pdf) (date accessed 4th October, 2012).
- [7]. ***a) Indian Standards for Drinking water, ISO 10500 <http://hppcb.gov.in/eiasorang/spec.pdf>
b) Indian Standards for Drinking water, ISO 10500 (1992) <http://hppcb.gov.in/eiasorang/spec.pdf> (date accessed 4th October, 2012) .
- [8]. *** http://www.nofluoride.com/Unicef_fluor.cfm (date accessed 25th February, 2013).
- [9]. V. Agrawal, A.K. Vaish and P. Vaish, Current Science **73**, 743 (1997).
- [10]. P.B. Maithani, R. Gurjar, R. Banerjee, B.K. Balaji, S. Ramachandran and R. Singh, Current Science **74**, 773 (1998).
- [11]. S. Priyanka, R. Bina, S. Upma and R. Mageshwari, Journal of Pharmaceutical and Biomedical Sciences **6**, 1 (2011).
- [12]. S. Ayoob, A.K. Gupta and T. Venugopal Bhat, Critical Reviews in Environmental Science and Technology **38**, 401 (2008).
- [13]. *** Application Notes on Indian Institute of Science Method of Defluoridation, http://civil.iisc.ernet.in/~msrao/files/application_IIScmethod.pdf (date accessed 25th February, 2013).

- [14]. S.M. Rao, P. Mamatha, K. Asha, K. Soumita and D.J. Mythri, *Water Management* **163**, 147 (2010)
- [15]. S.M. Rao and P. Mamatha. *Current Science* **87**, 942 (2004).
- [16]. K. Margandan, R. Agarwal, K. Singh, S. Sharma, K. Qanungo and R. Acharya, *Southern Brazilian Journal of Chemistry*, **21**, 79 (2013)
- [17]. S.M. Rao, P. Mamatha and B.V. Venkataram Reddy, 2004, Process for the treatment of fluorine-contaminated water and a domestic de-fluoridation unit. Indian Patent Application No. 614/CHE/2004.
- [18]. P. Mamatha and S.M. Rao, *Environmentalist* **31**, 39 (2011).
- [19]. M. Shihabudheen, Maliyekkal, K.R. Anshup and A.T. Pradeep, *Science of the Total Environment*, **408**, 2273 (2010).
- [20]. M. Shihabudheen, Maliyekkal, Sanjay Shukla, Ligy Philip and M. Indumathi, Nambi, *Journal of Chemical Engineering*, **140**, 183 (2008).
- [21]. B.D. Turner, P. Binning and S.L.S. Stipp, *Environment Science and Technology* **39**, 9561 (2005).
- [22]. A. Ghoshal, B. Mahapatra and A.K. Nad, 3rd Eds, *An Advanced Course in Practical Chemistry*, New Central Book Agency (P) Ltd., Calcutta, 2007.
- [23]. ***Acid-Base Equilibria and Solubility, By Laird, B.B., Eds. by Paul Ducham <http://mhanswers-auth.mhhe.com/chemistry/chemistry/acid-base-equilibria-and-solubility> (date accessed 25th May, 2013).
- [24]. ***P. Y. Duggirala, Formation of Calcium Carbonate Scale and Control Strategies in Continuous Digesters http://www.eucalyptus.com.br/icep02/prasad_duggirala.pdf (date accessed 25th May, 2013).

Submitted: February 25th 2013

Accepted in revised form: May 27th 2013